

Apex850

DYNAMIC CARDIOID

APPLICATIONS: Vocals, Announcements, Karaoke, Instruments

DESCRIPTION:

Apex dynamic handheld microphones are designed to provide an optimum, cost-effective solution to a wide variety of sound reinforcement, stage and recording applications. All are engineered to deliver smooth accurate response, full bottom end and sparkling highs with sound characteristics identical to those of similar, much higher-priced industry standard models.

FEATURES:

Ergonomics & Construction

Apex microphones are finished in textured, matte coating to reduce unwanted glare and provide a secure, non-slip grip. The heat treated metal ball grilles are soldered and welded to threaded bases to form extremely rugged assemblies which can withstand ten times the shock loading of traditional microphones. In addition to providing protection to the microphone, the grilles also serve to reduce extraneous noise via a multi-stage windscreen.

Design & Components

The Apex850 has a cardioid polar pickup pattern which enhances sound isolation by increasing sensitivity in the area in front of the microphone. This minimizes bleed-through from extraneous sound sources and reduces feedback. Additionally, proximity effect contributes to a fuller sound in most vocal models while a unique filter incorporated into the design reduces breath noise and the popping caused by explosive consonants such as 'B', 'P' and 'T'.


Cartridges

The patented Apex cartridges consist of a one-piece molded unit which provides exceptional reliability and durability. Computer-refined design precisely and permanently aligns the magnet, pole piece and yoke into a single rigid unit. This discrete component is extremely resistant to shock and allows the microphone to withstand the rough use associated with life on the road.

- Dynamic Cardioid Pickup Pattern
- Low Impedance
- On/Off Switch

POLAR PATTERN:

Cardioid



SPECIFICATIONS:

Type	Dynamic
Polar Pattern	Cardioid
Frequency Response	80Hz to 12kHz (+/- 3dB)
Sensitivity	-70dB (+/- 2dB @ 1kHz 0dB=1V/Pa)
Maximum Input SPL	130dB
Output Impedance	600 ohms
Signal to Noise Ratio	>45dB
Connector	3-pin XLR-M

ACCESSORIES:

XLR to XLR mic cable, microphone stand clip