

# Apex880

## DYNAMIC SUPER-CARDIOID

**APPLICATIONS:** Vocals, Announcements, Karaoke

### DESCRIPTION:

Apex dynamic handheld microphones are designed to provide an optimum, cost-effective solution to a wide variety of sound reinforcement, stage and recording applications. All are engineered to deliver smooth accurate response, full bottom end and sparkling highs with sound characteristics identical to those of similar, much higher-priced industry standard models.

### FEATURES:

#### Ergonomics & Construction

Apex microphones are finished in textured, matte coating to reduce unwanted glare and provide a secure, non-slip grip. The heat treated metal ball grilles are soldered and welded to threaded bases to form extremely rugged assemblies which can withstand ten times the shock loading of traditional microphones. In addition to providing protection to the microphone, the grilles also serve to reduce extraneous noise via a multi-stage windscreen.

Secure connections are assured through the use of high quality connectors and all cables include built-in strain relief fittings.

#### Design & Components

The Apex880 has a supercardioid polar pickup pattern which offers a narrower pick up pattern than Cardioid mics and are less prone to feedback and crosstalk in high volume environments. This minimizes bleed-through from extraneous sound sources and reduces feedback.


#### Cartridges

The patented Apex cartridges consist of a one-piece molded unit which provides exceptional reliability and durability. Computer-refined design precisely and permanently aligns the magnet, pole piece and yoke into a single rigid unit. This discrete component is extremely resistant to shock and allows the microphone to withstand the rough use associated with life on the road.

- Dynamic Super-Cardioid Pickup Pattern
- Low Impedance
- On/Off Switch

### POLAR PATTERN:

Supercardioid



### SPECIFICATIONS:

Type	Dynamic
Polar Pattern	Supercardioid
Frequency Response	80Hz to 12kHz (+/- 3dB)
Sensitivity	-70dB (+/- 2dB @ 1kHz 0dB=1V/Pa)
Maximum Input SPL	130dB
Output Impedance	600 ohms
Signal to Noise Ratio	>45dB
Connector	3-pin XLR-M

### ACCESSORIES:

XLR to XLR mic cable, microphone stand clip